



- COCL= Center of opening from cover left side
- COW = Clear opening width  
*Recom. (SBL-2xLAP-100)/2*  
*Min. 900, max. (SBL-2xLAP-G)/2*
- CL = Cover length incl 2x30 mm end plates  
*Recom. (2xCOW) + (2xLAP) + 100 + (2x30)*  
*Min. (2xCOW) + (2xLAP) + 60*
- DH = Door leaf height
- SBL = Support beam length  
*Recom. (2xCOW) + (2xLAP) + 100*  
*Min. (2xCOW) + (2xLAP), Max. 6100*
- LAP = Overlapping
- G= Space between door leaf and jamb
- DW= Door width (If door adaptor state DW)
- K= Clear opening width, fixed screens

State when ordering

COCL=.....mm

COW=.....mm

Cover

CL=.....mm

SBL=.....mm

LAP=.....mm

*If not stated LAP = 20*

G=.....mm

*If not stated G = 0*

DW=.....mm

Surface treatment

Silver anodized

Special anodized.....

RAL.....

Special powder coating .....

.....

Customer:	
Door id:	
Project No:	

Ref:	
Date:	
Sign:	

Sliding door operator  
 UniSlide-1 R/L (L shown)

Article No. 500335



6	833082
---	--------