



- COCL= Center of opening from cover left side
- COW = Clear opening width  
*Recom. (SBL-2xLAP-100)/2*  
*Min. 900, max. (SBL-2xLAP-G)/2*
- CL = Cover length incl 2x30 mm end plates  
*Recom. (2xCOW) + (2xLAP) + 100 + (2X30)*  
*Min. (2xCOW) + (2xLAP) + 60*
- DH = Door leaf height
- SBL = Support beam length  
*Recom. (2xCOW) + (2xLAP) + 100*  
*Min. (2xCOW) + (2xLAP), Max. 6100*
- LAP = Overlapping
- G= Space between closed door leaves
- DW= Door width (If door adaptor state DW)
- K= Clear opening width, fixed screens

State when ordering

- COCL=.....mm
- COW=.....mm
- Cover
- CL=.....mm
- SBL=.....mm
- LAP=.....mm
- If not stated LAP = 20*
- G=.....mm
- If not stated G = 0*
- DW=.....mm

Surface treatment

- Silver anodized
- Special anodized.....
- RAL.....
- Special powder coating.....
- .....

<b>Customer:</b>	
<b>Door id:</b>	
<b>Project No:</b>	

<b>Ref:</b>	
<b>Date:</b>	
<b>Sign:</b>	

Sliding door operator  
 UniSlide-2  
 Article No. 500337

6	833081